Global Pipe Manufacturer





Stainless Steel Flexible Gas Connectors with EFV

Complete selection of flexible connectors with automatic safety valve for gas appliances.



Stainless Steel Flexible Gas Connectors with EFV

Automatic Excess Flow Shut-off Connectors

In the case of a gas line rupture or a disconnect from the appliance, Easyflex EFV detects increase of gas flow and immediately shut-off the supply of gas. Gas flow is controlled only at the appliance where the problem exists. The valve will remain activated until the gas line is properly repaired.

- Automatically Activate
- Automatic Reset
- No battery needed
- 100% Performance Tested

Applications : Dryers, Boilers, BBQ Grills, Ranges/ Ovens, Furnaces, Fireplaces, Space Heaters, Tankless Water Heaters, Rooftop Units, Manufactured Homes

Availability

Types	 Stainless Steel (Uncoated) Yellow Epoxy Coated Stainless Steel Black Epoxy Coated Stainless Steel 		Lengths	12", 18", 24", 30", 36", 48", 60", 72"
Sizes	3/8" OD (1/4" ID)	1/2" OD (3/8" ID)	5/8" OD (1/2" ID)	1" OD (3/4" ID)
Fittings & Valves	1/2" MIP EFV (3/8"Tapped) 1/2" FIP EFV 1/2" FIP Ball Valve 1/2" FIP Angle Valve	3/8" MIP EFV(1/4"Tapped) 3/8" FIP EFV	3/4" MIP EFV(1/2"Tapped) 3/4" FIP EFV 3/4" FIP Ball Valve 3/4" FIP Angle Valve	1" MIP EFV(3/4"Tapped) 1" FIP EFV

Materials

- Tubing : Stainless Steel 304(ASTM A240)
- Fittings : Zinc-Plated Steel S45C

EEESYFLEX.

- EFV : Brass / Zinc- Plated Steel S45C
- Coating : Epoxy

Specifications

- Rated Pressure : 0.5 psi
- Rated Operating Temperature : -20°F to 150°F (-29°C to 65°C)

Certifications & Listings

- ANSI Z21.24 / CSA 6.10 Gas Appliances
- ANSI Z21.69 / CSA 6.16 Movable Gas Appliances
- ANSI Z21.75 / CSA 6.27 Outdoor Gas Appliances & Manufactured Homes
- ANSI Z21.93 / CSA 6.30 Excess flow valves for natural and LP gas with pressures up to 5 psig
- Commonwealth of Massachusetts Board of State Examiners
- City of New York-MEA #376-92-M

Global Pipe Manufacturer www.easyflexusa.com

WEST Office | Tel: 888-577-8999 | Fax: 714-892-2221 | info@easyflexusa.com EAST Office | Tel: 855-388-2600 | Fax: 201-331-3656 | info@easyflexeast.com

EFV •—-/	
	Excess Flow Valve (EFV)





Gastop

