

TRACWIN

*QINGDAO HILINE INDUSTRIAL CO., LTD.
No.288 Zhuhai Road, Huangdao District,
Qingdao, China.
www.tracwintire.com*



***TRACWIN BRAND
SEMI TRAILER (ST) SERIES
TIRES CATALOG 2023-2024***

SPECIAL FOR SEMI TRAILER (ST) SERIES



PATTERN TR202+

*High wear resistance and eccentric wear resistance.
Good heat release capacity.*

Excellent control ability performance.

Avoid champing stones.

Special use for semi trailer wheels only.

SIZE	PR	RIM	LOAD INDEX & SPEED	TREAD DEPTH	SECTION WIDTH	OVERAL DIA.	MAX LOAD (kg)		MAX PRESSURE (Kpa)	
				(mm)	(mm)	(mm)	SINGLE	DUAL	SINGLE	DUAL
ST11.00R20	20	8.0	156/153K	16	293	1085	3550	3250	930	930
ST11R22.5	20	8.25	156/150M	18.50	279	1054	3250	3000	830	830
ST12R22.5	20	9.00	156/153M	18	300	1085	4000	3650	930	930

SPECIAL FOR SEMI TRAILER (ST) SERIES



PATTERN TR256+

*High wear resistance and eccentric wear resistance.
Good heat release capacity.*

Excellent control ability performance.

Avoid champing stones.

Special use for semi trailer wheels only.

SIZE	PR	RIM	LOAD INDEX & SPEED	TREAD DEPTH	SECTION WIDTH	OVERAL DIA.	MAX LOAD (kg)		MAX PRESSURE (Kpa)	
				(mm)	(mm)	(mm)	SINGLE	DUAL	SINGLE	DUAL
ST11.00R20	20	8.0	156/153K	16	293	1085	3550	3250	930	930
ST11R22.5	20	8.25	156/150M	18.50	279	1054	3250	3000	830	830
ST12R22.5	20	9.00	156/153M	18	300	1085	4000	3650	930	930

SPECIAL FOR SEMI TRAILER (ST) SERIES



PATTERN TR316+

Distance in all various road in good condition.

Wide tread design makes long service life.

The casting has tiny pattern design that can effectively reduce noise and offer better heat dispersion, which sets up a more comfortable and safer driving environment.

Special use for semi trailer wheels only.

SIZE	PR	RIM	LOAD INDEX & SPEED	TREAD DEPTH	SECTION WIDTH	OVERAL DIA.	MAX LOAD (kg)		MAX PRESSURE (Kpa)	
				(mm)	(mm)	(mm)	SINGLE	DUAL	SINGLE	DUAL
ST11.00R20	20	8.0	156/153K	16	293	1085	3550	3250	930	930
ST11R22.5	20	8.25	156/150M	18.50	279	1054	3250	3000	830	830
ST12R22.5	20	9.00	156/153M	18	300	1085	4000	3650	930	930



PATTERN TR326+

The tire has three-groove and new pattern design that has great adhesion property..

Its strong wear-resistance compound design, has the running ability for lone distance.

Excellent comprehensive performance comes from special formula of low thermogenesis and good wear resistance.

Special use for semi trailer wheels only.

SIZE	PR	RIM	LOAD INDEX & SPEED	TREAD DEPTH	SECTION WIDTH	OVERAL DIA.	MAX LOAD (kg)		MAX PRESSURE (Kpa)	
				(mm)	(mm)	(mm)	SINGLE	DUAL	SINGLE	DUAL
ST11.00R20	20	8.0	156/153K	16	293	1085	3550	3250	930	930
ST11R22.5	20	8.25	156/150M	18.50	279	1054	3250	3000	830	830
ST12R22.5	20	9.00	156/153M	18	300	1085	4000	3650	930	930