



*QINGDAO HILINE INDUSTRIAL CO., LTD.
No.288 Zhuhai Road, Huangdao District,
Qingdao, China.
www.tracwintire.com*

***TRACWIN BRAND
TRUCK TIRE SERIES
CATALOG 2024***



PATTERN TR226

- *Wide tread design ensure excellent wear-resistance.*
- *It has four-line fore-and-aft sagittal groove design that can effectively avoid sideslip and offer good performance of handing.*
- *The tiny deep-groove pattern design of the side of the tread that can improve the ability of avoiding partial grinding.*
- *The brand-new tire shoulder low heat generation compound offers excellent high-speed performance.*
- *Special use for truck tyres.*

SIZE	PR	RIM	LOAD INDEX & SPEED	TREAD DEPTH	SECTION WIDTH	OVERAL DIA.	MAX LOAD (kg)		MAX PRESSURE (Kpa)	
				(mm)	(mm)	(mm)	SINGLE	DUAL	SINGLE	DUAL
11.00R20	20	8.0	156/153J	18.50	293	1085	3550	3250	930	930
11R22.5	20	8.25	156/150M	18.50	279	1054	3250	3000	830	830
12R22.5	20	9.00	156/153M	18	300	1085	4000	3650	930	930



PATTERN TR311

- *Special block pattern ensure the excellent braking ability.*
- *Deep groove design and good wear-resistance compound ensures long service life.*
- *Good anti-shock function and heat dispersion performance.*
- *Special use for truck tyres.*

SIZE	PR	RIM	LOAD INDEX & SPEED	TREAD DEPTH	SECTION WIDTH	OVERAL DIA.	MAX LOAD (kg)		MAX PRESSURE (Kpa)	
				(mm)	(mm)	(mm)	SINGLE	DUAL	SINGLE	DUAL
11R22.5	20	8.25	156/150M	18.50	279	1054	3250	3000	830	830
12R22.5	20	9.00	156/153M	18	300	1085	4000	3650	930	930



PATTERN TR318

- *The tire has big block mixed and deep pattern that has a wider running surface.*
- *It has stronger traction performance and grasping ability.*
- *The tire has great structure that owns good carrying capability.*
- *Its good wear-resistance and puncture-resistance compound ensure its long service life.*
- *Special use for truck tyres.*

SIZE	PR	RIM	LOAD INDEX & SPEED	TREAD DEPTH	SECTION WIDTH	OVERAL DIA.	MAX LOAD (kg)		MAX PRESSURE (Kpa)	
				(mm)	(mm)	(mm)	SINGLE	DUAL	SINGLE	DUAL
11.00R20	20	8.0	156/153J	18.5	293	1085	3550	3250	930	930
12.00R20	20	8.5	156/153J	20	315	1125	4000	3650	900	900
11R22.5	20	8.25	156/150M	18.50	279	1054	3250	3000	830	830
12R22.5	20	9.00	156/153M	18	300	1085	4000	3650	930	930



PATTERN TR328

- *The tread pattern is specially designed to have a stronger holding power*
- *Its deep pattern ensure the tire a longer service life.*
- *The stout pattern block design makes the tire has a good adaptability for all kinds of roads.*
- *The special pattern groove protects the running tire from puncturing.*
- *Special use for truck tyres.*

SIZE	PR	RIM	LOAD INDEX & SPEED	TREAD DEPTH	SECTION WIDTH	OVERAL DIA.	MAX LOAD (kg)		MAX PRESSURE (Kpa)	
				(mm)	(mm)	(mm)	SINGLE	DUAL	SINGLE	DUAL
11.00R20	20	8.0	156/153J	18.5	293	1085	3550	3250	930	930
12.00R20	20	8.5	156/153J	20	315	1125	4000	3650	900	900
11R22.5	20	8.25	156/150M	18.50	279	1054	3250	3000	830	830
12R22.5	20	9.00	156/153M	18	300	1085	4000	3650	930	930



PATTERN TR726

- *Special block pattern ensure the excellent braking and driving ability.*
- *Deep groove design and good wear-resistance compound ensures long service life.*
- *Good anti-shock function and heat dispersion performance.*
- *Suitable for middle and long vehicles in both pavements in bad conditions and normal grade road.*
- *Special use for truck tyres.*

SIZE	PR	RIM	LOAD INDEX & SPEED	TREAD DEPTH	SECTION WIDTH	OVERAL DIA.	MAX LOAD (kg)		MAX PRESSURE (Kpa)	
				(mm)	(mm)	(mm)	SINGLE	DUAL	SINGLE	DUAL
11.00R20	20	8.0	156/153J	18.50	293	1085	3550	3250	930	930
11R22.5	20	8.25	156/150M	18.50	279	1054	3250	3000	830	830
12R22.5	20	9.00	156/153M	18	300	1085	4000	3650	930	930



PATTERN TR751

- *The special designed tread pattern ensures good grip strength.*
- *Its deep pattern ensures longer tire life.*
- *The stout pattern block design makes the tires has a good adaptability for all kinds of roads.*
- *Specially compound design for mixing tread pattern provides wear-resistance.*
- *Special use for truck tyres.*

SIZE	PR	RIM	LOAD INDEX & SPEED	TREAD DEPTH	SECTION WIDTH	OVERAL DIA.	MAX LOAD (kg)		MAX PRESSURE (Kpa)	
				(mm)	(mm)	(mm)	SINGLE	DUAL	SINGLE	DUAL
12R22.5	20	9.00	156/153M	18	300	1085	4000	3650	930	930

PATTERN HDC09



- *The large shoulder pattern is supplemented by a stiffener design, which has good cut and tear resistance.*
- *The open wide groove design gives the tire good self-cleaning and heat dissipation.*
- *The special tread formula and reasonable sea-to-land ratio design provide excellent wear resistance.*
- *Enhanced sub-port design, excellent product load-bearing.*
- *Special use for truck tires.*

SIZE	PR	RIM	LOAD INDEX & SPEED	TREAD DEPTH	SECTION WIDTH	OVERAL DIA.	MAX LOAD (kg)		MAX PRESSURE (Kpa)	
				(mm)	(mm)	(mm)	SINGLE	DUAL	SINGLE	DUAL
12R22.5	20	9.00	152/149L	20	300	1085	4000	3650	930	930